Accomplishments of the International Criticality Safety Benchmark Evaluation Project (ICSBEP) During 2010

J. Blair Briggs
Presented by ***John D. Bess***
Idaho National Laboratory (INL)

DOE Workshop: "NCSP Accomplishments
2011 ANS Annual Meeting
Hollywood, Florida
July 1, 2011

www.inl.gov
Idaho National Laboratory

Outline

- Publication of the 2010 Edition of the ICSBEP Handbook
- 25 newly approved benchmark evaluations
  - 12 from the United States
  - 13 from outside the United States
- Upgrades to ICSBEP database and user interface, DICE

International Handbook of Evaluated Criticality Safety Benchmark Experiments

- **September 2010 Edition**
  - 20 Contributing Countries
  - Spans nearly 55,000 Pages
  - Evaluation of 516 Experimental Series
  - 4,405Critical or Subcritical Configurations
  - 24 Criticality-Alarm/Shielding Benchmark Configurations – numerous dose points each
  - 155 fission rate and transmission measurements and reaction rate ratios for 45 different materials
  - 25 New Evaluations in 2010

  - http://icsbep.inl.gov



ORALLOY (93.15 ^{235}U) Metal Annuli with Beryllium Core (HEU-MET-FAST-059) – INL



ORALLOY (93.2 ^{235}U) Metal Cylinder with Beryllium Top Reflector (HEU-MET-FAST-069) – INL



Polyethylene-Reflected Arrays of HEU(93.2) Metal Units Separated by Vermiculite (HEU-MET-FAST-056) – INL / ISU



Concrete Reflected Arrays of U(93.2) Metal (HEU-MET-FAST-054) – INL / ISU



Dimensions in cm

Water-Moderated and -Reflected Slabs of Uranium Oxyfluoride (HEU-SOL-THERM-034) – INL / University of Utah





Perspective view
(Not to scale)

2 x 2 Polyethylene Reflected and Moderated Highly Enriched Uranium System with Rhenium (HEU-MET-THERM-033) – ENE



2 x 2 x 13 Array of Highly Enriched Uranium with NI-CR-MO-GD Alloy, Moderated and Reflected by Polyethylene (HEU-MET-THERM-034) – WSMS



ZPR-3 Assembly 6F: A Spherical Assembly of Highly Enriched Uranium, Depleted Uranium, Aluminum and Steel with an Average ^{235}U Enrichment of 47 Atom % (IEU-MET-FAST-015) – ANL



ZPR-3 Assembly 11: A Cylindrical Assembly of Highly Enriched Uranium and Depleted Uranium with an Average ^{235}U Enrichment of 12 Atom % and a Depleted Uranium Reflector (IEU-MET-FAST-016) – ANL



ZPR-3 Assembly 12: A Cylindrical Assembly of Highly Enriched Uranium, Depleted Uranium and Graphite with an Average ^{235}U Enrichment of 21 Atom % (IEU-COMP-FAST-004) – ANL



U(4.89) Metal Rods in Water or Uranyl Fluoride Solution (LEU-MET-THERM-007) – DOE-OR / ORNL / University of Tennessee



D_2O MODERATED LATTICE of $^{233}UO_2$-$^{232}ThO_2$ (U233-COMP-THERM-004) – WSMS



One Dimensional Array of Highly Enriched Uranium, Moderated and Reflected by Polyethylene (HEU-MET-THERM-032) – JSI, Slovenia



HEU Cylinders Axially Reflected by Steel (HEU-MET-FAST-043) or Aluminum (HEU-MET-FAST-044) – VNIITF, Russia



Azimuthal symmetry with respect to the Z-axis

Dimensions in cm

10-GA50002-131-6

Heterogeneous Iron-Diluted (HEU-MET-FAST-087) or Aluminum-Diluted (HEU-MET-FAST-089) HEU Cylinder – VNIITF, Russia



Highly Enriched Uranium Cylinder Reflected by Polyethylene (HEU-MET-FAST-091) – VNIITF, Russia



RA-6 Reactor: Water Reflected, Water Moderated U(19.77)3Si2-Al Fuel Plates (IEU-COMP-THERM-014) – CNEA, Argentina



Bare and Water-Reflected Spheres and Hemispheres of Aqueous Uranyl Fluoride Solutions (30.45% ^{235}U) (IEU-SOL-THERM-002) – AWE, United Kingdom

Early Pioneers

Members of the Dounreay criticality team in front of Cell 1 (with US visitors) – May 1959.
From left: Vic Parker, Eric Thornthwaite, Alan Bray, J. C. Smith, Gordon Hansen, Hugh Paxton, John Walford, Roy Reider, Jimmy Lyons, Bob Hack, George White.
(Hansen, Paxton and Reider were visiting from LASL.)

4.738-WT.%-Enriched Uranium Dioxide Fuel Rod Arrays Reflected by Water in a Dry Storage Configuration (IEU-COMP-THERM-057) – IRSN, France

Aluminum Box Contains

- Air
- Water
- Polystyrene
- Polyethylene



VVER Physics Experiments: Regular Hexagonal (1.27 cm Pitch) Lattices of Low-Enriched U(3.5 WT.% $^{235}U)O_2$ Fuel Rods in Light Water at Different Core Critical Dimensions (LEU-COMP-THERM-030) –

RRC Kurchatov Institute, Russia



Critical Loading Configurations of the IPEN/MB-01 Reactor with Large Void in the Reflector (LEU-COMP-THERM-058) – IPEN, Brazil



STACY: A 60-CM-Diameter Tank Containing 5%-Enriched UO_2 Fuel Rods (2.5-cm Square Lattice Pitch) in 6%-Enriched Uranyl Nitrate Solutions, Unreflected and Water-Reflected (LEU-MISC-THERM-007) – JAEA, Japan



BFS-61 Assemblies: Critical Experiments of Mixed Plutonium, Depleted Uranium, Graphite and Lead with Different Reflectors (MIX-MET-FAST-006) – IPPE. Russia



- Core (277)
- Lead, canned (66)
- Lead, uncanned (246)
- Stainless steel (222)
- $U(d)O_2$ (587)
- Empty tube (77)
- SS bar

All intertubular gaps in the reflector outside the dotted line were filled with stainless steel bars

MIX-MET-FAST-006 (Continued) – Unit Fuel Cell



Dimensions in cm

10-GA50002-111-3

Database for the International Criticality Safety Benchmark Evaluation Project (DICE)

- Upgrades and Corrections
- Data Verification Efforts
- Workshop Planned for ICNC-2011